(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 19 May 2005 (19.05.2005)

(10) International Publication Number WO 2005/044928 A1

(51) International Patent Classification7: 5/24, C23F 13/02, 13/06

C09D 5/10.

(21) International Application Number:

PCT/US2004/035250

(22) International Filing Date: 22 October 2004 (22.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/514,691

27 October 2003 (27.10.2003)

- (71) Applicant (for all designated States except US): POLY-ONE CORPORATION [US/US]; 33587 Walker Road, Avon Lake, OH 44012 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): AVAKIAN, Roger, W. [US/US]; 170 Cambridge Drive, Aurora, OH 44202 (US). HORTON, Stephen, D. [US/US]; 33486 Vineyard Park, Avon, OH 44011 (US). HORNICKEL, John, H. [US/US]; 4220 State Road, Medina, OH 44256 (US).
- (74) Common Representative: POLYONE CORPORA-TION; 33587 Walker Road, Avon Lake, OH 44012 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CATHODIC PROTECTION COATINGS CONTAINING CARBONACEOUS CONDUCTIVE MEDIA

(57) Abstract: A cathodic protection polymeric compound is disclosed. The compound has flowable material to serve as a binder, carbonaceous conductive media dispersed in the flowable material, sacrificial metal particles also dispersed in the flowable material. The carbonaceous conductive media serve as a carbon-based electron transfer agent and are in the form of particles, platelets, fibers, tubes, or combinations thereof. A galvanic circuit is formed by the metal particles serving as anodes, a metal substrate to be protected serving as the cathode, and the conductive media serving as the electron transfer agent. The flowable material can also include an ionically conductive or an inherently conductive polymer to further enhance the galvanic circuit.

